

Company:  Power Supply Co.,LTD

Add:XiChong Complex,Lunjiao Town,Shunde District,Foshan City,Guangdong Province.

24V 5A/36V3.33A for 300-400G RO System

Desktop Power Supply Feature:

Universal Input Voltage

No Load Power Consumption:<0.5W

Single Output

Optional Output Connectors

Short Circuit Protection

Over voltage protection

High efficiency & Reliability

Built-in low input voltage cut off function

High input power factor

Low input ATHD

Three Years Limited Warranty



Safety Approvals:



Specifications:

Input Voltage	100 ~ 240 VAC
Input Frequency	50 ~ 60Hz (Limits : 47 ~ 63 Hz)
Input Current	2.5A Max.
Safety Ground Leakage Current	0.25mA Max@3.5mA MAX
Output Voltage	24V/36V
Output Current	5A/3.33A
Output Power Range	120W MAX
Ripple	1% peak to peak maximum.
Over Voltage Protection	Yes.Protected by Zener diode
Over Current Protection	Yes. Auto - recovery. Standard Series : Rated output current > 110% for primary-referenced direct drive (Constant current series : Rated output current 80~200% for secondary-referenced direct drive)
Short Circuit Protection	Yes. Hiccup mode; Auto-recovery
Operating Temperature	-20 °C ~ +45°C.
Storage Temperature	-20°C~ +85°C
Relative Humidity	5% to 95% non-condensing
Setup up / Hold up / Rise time	Typical : 3000mS / 16mS / 50mS at full load.
Line Regulation	±1% maximum for any input voltage change between input voltage range
Load Regulation	Typical + 5% variations from minimum to maximum output current .
Insulation Resistance	50Mohm minimum from input to ground
Inrush Current	30 AMPS @ 240 VAC at 25 °C cold start
Withstand Voltage	4242VDC from input to output
Mean Time between Failure	100,000 hours minimum at full load at 25°C ambient
Safety Requirements	CE, FCC, UL,CUL,PSE,GS,CCC,KC
Warranty	3 Years

E-mail:winnie@gve-cn.com, adam@gve-cn.com
Tel:+86 757 2773 6306 Fax:+86 757 27725706
Cell Phone:86 138 2557 1248/ 138 2557 4248